

GRIGGS PAINT -- A-A-1452B #17875 GLOSS WHITE 700W142 -- 8010-00-166-1667  
===== Product Identification =====

Product ID:A-A-1452B #17875 GLOSS WHITE 700W142

MSDS Date:01/01/1999

FSC:8010

NIIN:00-166-1667

Status Code:A

MSDS Number: CLKNN

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phon

e Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

===== Composition/Information on Ingredients =====

Ingred Name:DIOCTYL PHTHALATE

CAS:117-81-7

RTECS #:TI0350000

= Wt:5.

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

ACGIH STEL:10 MG/M3

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred N

ame:CYCLOHEXANONE

CAS:108-94-1

RTECS #:GW1050000

= Wt:5.

OSHA PEL:200 MG/M3;50 PPM

ACGIH TLV:100 MG/M3;25 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000

= Wt:6.

OSHA PEL:465 MG/M3;100 PPM

ACGIH TLV:233 MG/M3;50 PPM

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

= Wt:7.

OSHA PEL:710 MG/M3;150 PPM

ACGIH TLV:713 MG/M3;150 PPM

ACGIH STEL:950 MG/M3;200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE

CAS:67-6

4-1

RTECS #:AL3150000

= Wt:18.

OSHA PEL:2400 MG/M3;1000 PPM

ACGIH TLV:1780 MG/M3;750 PPM

ACGIH STEL:2380 MG/M3;1000 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES MAY CAUSE

IRRITATION. PROLONGED AND/OR REPEATED CONTACT MAY CAUSE SKIN

IRRITATION. INHALATION OF HIGH CONCENTRATIONS OF VAPORS MAY LEAD TO

LUN



ons:MAINTAIN GOOD HYGIENE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MSHA/NIOSH APPROVED UNITS.  
Ventilation:LOCAL AND MECHANICAL EXHAUST.  
Protective Gloves:RUBBER GLOVES.  
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.  
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.  
Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

B  
Boiling Pt:B.P. Text:131 TO 724 DEG F  
Melt/Freeze Pt:M.P/F.P Text:NONE  
Decomp Temp:Decomp Text:NONE  
Vapor Density:HEAVIER  
Spec Gravity:H2O=1: 1.1  
VOC Pounds/Gallon:373  
VOC Grams/Liter:3.11  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:ESSENTIALLY NIL  
Appearance and Odor:VISCIOUS LIQUID WITH STRONG SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:  
d:FLAMES, SPARKS, SMOKING AND HEAT.  
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.  
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE  
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States

of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.