

COURTAULDS AEROSPACE INC -- MANGANESE DIOXIDE DISPERSION PR1750 B-2 --
8030-00-560-8758

===== Product Identification =====

Product ID:MANGANESE DIOXIDE DISPERSION PR1750 B-2

MSDS Date:09/30/1996

FSC:8030

NIIN:00-560-8758

Status Code:A

MSDS Number: CLKYH

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:HYDROGENATED TERPHENYL

CAS:061788-32-7

= Wt:30.

OSHA PEL:0.5 PPM

A

CGIH TLV:0.5 PPM

Ingred Name:CARBON BLACK
CAS:001333-86-4
= Wt:10.
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

Ingred Name:MANGANESE DIOXIDE
CAS:001313-13-9
= Wt:55.
OSHA PEL:5 CEILING MG/M3
ACGIH TLV:5 AS MN MG/M3

Ingred Name:DIPHENYL GUANIDINE GUANIDINE,N,N, DIPHENYL
CAS:000102-06-7
< Wt:5.

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Health Hazards Acute and Chronic:NONE
Effects of Overexposure:EYES: SEVERELY IRRITATING. SKIN: TOXIC BY SKIN

ABSORPTION. MAY BE A SENSITIZER. INHALATION: AIRBORNE MATERIAL MAY
PRODUCE IRRITATION, AND MAY BE ABSORBED THROUGH THE LUNGS.
INGESTION: TOXIC ON ORAL C ONSUMPTON.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. SKIN: WASH
WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS
ARE PRESENT CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN.

==

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=157.2C, 315.F
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.
Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE DECOMPOSITION OF
MANGANESE DIOXIDE, RESULTING IN OXIDATION AND POSSIBLE IGNITION OF
HYDROCARBON VEHICLE.

=====

==== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS.
Neutralizing Agent:NONE

==== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND
BEFORE SMOKING OR EATING.
Other Precautions:NONE

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:GENERAL VENTILATION.
Protective Gloves:SOLVENT GLOVES.
Eye Protection:SA
FETY GLASSES.
Other Protective Equipment:NONE
Work Hygienic Practices:NONE
Supplemental Safety and Health
NONE

==== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:644-644 DEG F
Melt/Freeze Pt:M.P/F.P Text:NONE
Decomp Temp:Decomp Text:NONE
Spec Gravity:1.97
Appearance and Odor:BLACK PASTE

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN,
MANGANESE COMPOUNDS.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

==== Disposal Considerations =====

Waste Disposal Methods:CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF
SPILLAGE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.