

COURTAULDS AEROSPACE INC -- POLYSULFIDE RUBBER COMPOUND PR1750 B-2 (MIXED)
#1750B131 -- 8030-00-560-8758

===== Product Identification =====

Product ID:POLYSULFIDE RUBBER COMPOUND PR1750 B-2 (MIXED) #1750B131

MSDS Date:10/21/1996

FSC:8030

NIIN:00-560-8758

Status Code:A

MSDS Number: CLKYJ

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO RD

Box:1800

City:GLEN

DALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:013463-67-7

< Wt:5.
OSHA PEL:10 MG?M3
ACGIH TLV:10 MG?M3

Ingred Name:CALCIUM CARBONATE@LIMESTONE
CAS:001317-65-3
= Wt:30.
OSHA PEL:15.0 MG/M3
ACGIH TLV:10.0 MG/M3

Ingred Name:TOLUENE
CAS:000108-88-3
< Wt:1.
OSHA PEL:100 PPM
OSHA STEL:150
ACGIH TLV:50 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Health Hazards Acute and Chronic:CHRONIC EXPOSURE MAY CAUSE DISTURBANCE
IN MEMORY, THINKING ABILITY, EMOTIONS, COORDINATION.
Effects of Overexposure:E
YES: MAY CAUSE BURNING. TEARING AND REDDENING.
SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN, AND
POSSIBLE DERMATITIS. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS
AND NAUSEA.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. CONSULT A PHYSICIAN. SKIN: WASH WITH
SOAP AND WATER. CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH
AIR. CONSULT A PHYSICIAN. INGESTION: DRINK
LARGE AMOUNTS OF WATER;
INDUCE VOMITING, CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:=93.3C, 200.F
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SCOO

P INTO CONTAINERS. CLEAN UP RESIDUE WITH A
SUITABLE SOLVENT.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND
BEFORE SMOKING OR EATING. AVOID INGESTION.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:GENERAL VENTILATION.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GLASS
ES.

Other Protective Equipment:NONE

Work Hygienic Practices:NONE

Supplemental Safety and Health
NONE

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230-350 DEG F

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Density:HEAVIER

Spec Gravity:1.571

Evaporation Rate & Reference:SLOWER THAN N-BUTYL ACETA

Appearance and Odor:V.O.C. PER EPA METHOD 24.

Percent Volatiles by Volume:3.3%

=====
===== Stability and Reactivity Data =

Stability Indicator/Materials to Avoid:YES
NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE,
TRACES OF HYDROGEN SULFIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF
SPILLAGE.

Disclaimer (provided with this information by the compiling agencies):
This information is fo

rmulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.