

GRIGGS PAINT -- TT-L-32A #17875 WHITE LACQUER -- 8010-00-242-6315

=====
Product Identification
=====

Product ID:TT-L-32A #17875 WHITE LACQUER

MSDS Date:10/28/1998

FSC:8010

NIIN:00-242-6315

Status Code:A

MSDS Number: CLLJM

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

=====
Composition/Information on Ingredients
=====

Ingred Name:DIOCTYL PHTHALATE

CAS:117-81-7

RTECS #:TI0350000

< Wt:2.

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

ACGIH STEL:10 MG/M3

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:CYCLOHE

XANONE
CAS:108-94-1
RTECS #:GW1050000
< Wt:5.
OSHA PEL:200 MG/M3;50 PPM
ACGIH TLV:100 MG/M3;25 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL AMYL KETONE
CAS:110-43-0
RTECS #:MJ5075000
< Wt:5.
OSHA PEL:465 MG/M3;100 PPM
ACGIH TLV:233 MG/M3;50 PPM

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
< Wt:5.
OSHA PEL:710 MG/M3;150 PPM
ACGIH TLV:713 MG/M3;150 PPM
ACGIH STEL:950 MG/M3;200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE
CAS:67-64-
1
RTECS #:AL3150000
= Wt:19.
OSHA PEL:2400 MG/M3;1000 PPM
ACGIH TLV:1780 MG/M3;750 PPM
ACGIH STEL:2380 MG/M3;1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES MAY CAUSE
IRRITATION. PROLONGED AND/OR REPEATED CONTACT MAY CAUSE SKIN
IRRITATION. INHALATION OF HIGH CONCENTRATIONS OF VAPOR

S MAY LEAD TO

LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION, AND CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHAL;ATION: HIGH VAPOR MAY CAUSE DROWSINESS, DIZZINESS, FATIGUE, FOLLOWED BY COMA. EYE: DIRECT CONTACT AND/OR CONTACT WITH VAPORS MAY CAUSE IRRITATION. SKIN: PROLONGED AND/OR REPEATED CONTACT MAY CA USE IRRITATION AND/OR DERMATITIS. INGESTION M

AY CAUSE GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN CENTRAL NERVOUS SYSTEM, LIVER AND KIDNEY.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEEK MEDICAL AID.SKIN: WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL AID. INGESTION: IMMEDIATELY SEEK MEDICAL AID.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:=-20.C, -4.F

-4 DEG F.

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:0.3%

Upper Limits:7.9%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONEL. WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSE

D. ISOLATE

FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER.

Neutralizing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS

CLOSED AND UPRIGHT TO
PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID
BREATHING OF VAPOR AND SPRAY MIST. AVOID SKIN AND EYE CONTACT.
Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN
CONFINED AREAS, TANK OR PIT, WITHOUT ADEQUATE VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION
EXPOSURES BELOW TLV (PEL), USE MSHA/NIOSH APPROVED UNITS.

Ventilation:LOCAL AND MECHANICAL EXHAUST.
Protective Gloves:RUBBER GLOVES.
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE.

Supplemental Safety and Health
AS THE CONDITIONS OR METHODS ARE BEYOND OUR CONTROL, WE DO NOT ASSUME
ANY RESPONSIBILITY REGARDING USE OF PRODUCT. WE EXPRESSLY DISCLAIM
ANY LIABILITY FOR ANY USE OF THE MATERIAL. INFORMATION CONTAINED
HEREIN IS BELIEVED TO BE
ACCURATE ALL STATEMENTS OR SUGGESTIONS.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:131 TO 724 DEG F.
Melt/Freeze Pt:M.P/F.P Text:NONE
Decomp Temp:Decomp Text:NONE
Vapor Density:HEAVIER
Spec Gravity:(H2O=1): 1.1
VOC Pounds/Gallon:360
VOC Grams/Liter:3.
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:ESSENTIALLY NIL.
Appearance and Odor:VISCOUS LIQUID WITH STRONG SOLVENT ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:FLAMES, SPARKS, SMOKING AND HEAT.
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIALS ON SPILLS.DISPOSE
OF IN ACCORDANCE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with t

his information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.