

STIC-ADHESIVE PRODUCTS CO INC -- PAINT, LATEX, TT-P-19D EXTERIOR, TT-P-29K INTERIOR --  
8010-00-598-5733

===== Product Identification =====

Product ID:PAINT, LATEX, TT-P-19D EXTERIOR, TT-P-29K INTERIOR

MSDS Date:07/01/1996

FSC:8010

NIIN:00-598-5733

Status Code:A

MSDS Number: CLLKH

=== Responsible Party ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

City:LOS ANGELES

State:CA

ZIP:90063-1675

Country:US

Emergency Phone Num:999-999-9999

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:1BH90

=== Contractor Identification ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

Box:City:LOS ANGELES

State:CA

ZIP:90063-1675

Country:US

CAGE:1BH90

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL

CAS:00057-55-6

&lt; Wt:5.

Ingred Name:TEXANOL ESTER ALCOHOL

CAS:25265-77-4

Code:F

RTECS #:UF600000

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION:VAPOR AND SPRAY MIST MAY BE HARMFUL IF INHALED. VAPOR GENERATED AT ELEVATED TEMPERATURES IRRITATES EYES, NOSE AND THROAT. EYE CONTACT: DIRECT CONTACT MAY CAUSE EYE IRRITATION, REDNESS, AND TEARING. SKIN CONTACT: PROLONGED CONTACT MAY CAUSE TRANSIENT REDDENING OF THE SKIN.

INGESTION: HARMFUL OR FATAL IF SWALLOWED.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:NONE

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN, AND RESPIRATORY SYSTEM DISORDERS, AND UNUSUAL ALLERGIC SENSITIVITY.

=====  
First Aid Measures  
=====

First Aid:INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SKIN CONTACT: IN CASE OF SKIN CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOLLOWED BY WASHING WITH SOAP AND WATER. INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION AND OTHER SUPPORTIVE MEASURES AS REQUIRED.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC

Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR UNIVERSAL AQUEOUS FILM FORMING FOAM) DESIGNED TO EXTINGUISH NFPA CLASS 111B COM

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED. FOG NOZZLES ARE PREFERABLE. FIRE-FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE OR BURST (DUE TO THE BUILDUP OF PRESSURE)

ILD UP OF STEAM PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND ABSORB SPILLED LIQUID WITH INERT MATERIAL SUCH AS CLAY GRANULES, SAND, EARTH, OR SAWDUST. USE RAGS TO CLEAN UP SMALL AMOUNTS OF SPILLED MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, FLAME, OR STRONG OXIDIZERS, ACIDS AND ALKALIS. STORE IN COOL, WELL VENTILATED AREA. ROTATE STOCK USE OLDER MATERIAL FIRST. INSPECT ALL CONTAINERS FOR LEAKS.

Other Precautions:DO NOT STORE IN AREAS SUBJECT TO FREEZING TEMPERATURES. KEEP ABOVE 40 F AT ALL TIMES. USE ONLY WITH ADEQUATE VENTILATION OR PROTECTION. AVOID BREATHING SPRAY MIST OR VAPOR. DO NOT INGEST. AVOID CONTACT WITH SKIN. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR SPRAY APPLICATION, USE PARTICULATE FILTER MASK TO AVOID BREATHING SPRAY MIST EXPOSED PERSONS WITH UNUSUAL ALLERGIC SENSITIVITY MAY NEED ORGANIC VAPOR RESPIRATOR (NIOSH/MSHA TC 23C EQUIVALENT).

Ventilation:FOR INTERIOR USE, GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO DISPERSE VAPOR. OTHERWISE OPEN DOORS AND WINDOWS OR USE PORTABLE FANS.

Protective Gloves:USE WATERPROOF GLOVES.

Eye Protection:USE SAFETY GLASSES, GOGGLES, OR FACE SHIELD TO PROTECT EYES.

Other Protective Equipment:WATERPROOF HEADCOVERING AND GENERAL PROTECTIVE CLOTHING ARE RECOMMENDED FOR PROTECTION AS NECESSARY.

Work Hygienic Practices:WASH HANDS AND FACE BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health  
NONE.

===== Physical/Chemical Properties =====

Boiling Pt.=100.C, 212.F

Vapor Density:HEAVIER

Spec Gravity:1.2-1.4

Evaporation Rate & Reference:(BUOAC=100):