

DEL PAINT MFG -- LATEX PROLINE WHITE -- 5920-01-238-7449

=====
Product Identification
=====

Product ID:LATEX PROLINE WHITE
MSDS Date:06/21/1999
FSC:5920
NIIN:01-238-7449
Status Code:A
MSDS Number: CLLZF
=== Responsible Party ===
Company Name:DEL PAINT MFG
Address:3105 EAST RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Info Phone Num:405-672-1431
Emergency Phone Num:1-800-424-9300
Preparer'
s Name:ERNEST CARTER
Chemtre Ind/Phone:(800)424-9300
CAGE:39934

==== Contractor Identification ====

Company Name:DEL PAINT MFG
Address:3105 EAST RENO
Box:City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431
CAGE:39934

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL
CAS:107-21-1
RTECS #:KW2975000
= Wt:.94
ACGIH STEL:C127 MG/M3;C50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

====

Routes of Entry: Inhalation:UNKNOWN Skin:UNKNOWN Ingestion:YES
Effects of Overexposure:MAY CAUSE SOME NAUSEA IF INGESTED.

=====
===== First Aid Measures =====

First Aid:IF INGESTED: GIVE 2 GLASSES OF WATER AND INDUCE VOMITING BY
PUTTING FINGER DOWN THROAT. SKIN: FLUSH WITH WATER. EYES FLUSH
WITH WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=116.1C, 241.F
Lower Limits:3.2%
Exting
uishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG,
Unusual Fire/Explosion Hazard:THE PRODUCT WILL NOT BURN UNTIL WATER
HAS EVAPORATED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE ABOVE 32 F.
Other Precautions:DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF
CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE
SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APPLICATION.
Ventilation:NORMAL SUCH AS FAN.
Protective Gloves:PROTECTIVE GLOVES: DESIRABLE.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:EYE BATH.
Work Hygienic Practices:WASH HANDS AND FACE BEFORE EATING.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

=====

Boiling Pt:B.P. Text:212-387 F
Vapor Density:HEAVIER
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:71.63%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:RESIDUALS CAN BURN AND PRODUCE CARBON
MONOXIDE & CARBON DIOXIDE.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposa
I Methods:BURY IN A LANDFILL WHERE PERMITTED UNDER
APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice
to verify and
assume responsibility for the suitability of this information to their
particular situation.