

DEXSIL CHEMICAL CORP -- AMPULE 2, CLOR-N-OIL 500 PCB SCREENING KIT (SUPPL) --  
6630-01-210-8162

===== Product Identification =====

Product ID:AMPULE 2, CLOR-N-OIL 500 PCB SCREENING KIT (SUPPL)

MSDS Date:06/05/1995

FSC:6630

NIIN:01-210-8162

Status Code:A

Kit Part:Y

MSDS Number: CLMSH

=== Responsible Party ===

Company Name:DEXSIL CHEMICAL CORP

Address:1 HAMDEN PARK DRIVE

City:HAMDEN

State:CT

ZIP:0651

4-3150

Country:US

Info Phone Num:203-288-3509

Emergency Phone Num:800-424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:65297

=== Contractor Identification ===

Company Name:DEXSIL CORP

Address:1 HAMDEN PARK DR

Box:City:HAMDEN

State:CT

ZIP:06514-3150

Country:US

Phone:203-288-3509

CAGE:65297

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHALENE

CAS:91-20-3

RTECS #:OJ0525000

Fraction by Wt: 50%MG/DGY

Other REC Limits:50 MG NAPIN DIGLYME

OSHA PEL:50 MG/M3;10 PPM

ACGIH TLV:52 MG/M3;10 PPM  
ACGIH STEL:79 MG/M3;15 PPM  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:DIGLYME  
CAS:111-96-6  
RTECS #:KN3339000

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:MANUFACTURER DOES NOT PROVIDE HEALTH  
HAZARD DATA. DSCR HOWEVER RECOMMENDS;TARGET ORGANS:EYES, SKIN,  
RESPIRATORY & GI TRACTS. ACUTE- INHALE:MAY CAUSE IRRITATION OF  
RESPIRATORY TRACT.  
EYE:MAY CAUSE IRRITATION. SKIN:MAY CAUSE  
DEFATTING. ORAL:MAY BE HARMFUL IF INGESTED. CHRONIC- UNKNOWN.  
Effects of Overexposure:TARGET ORGANS:EYES, SKIN, RESPIRATORY & GI  
TRACTS. ACUTE- INHALE:MAY CAUSE IRRITATION OF RESPIRATORY TRACT.  
EYE:MAY CAUSE IRRITATION. SKIN:MAY CAUSE DEFATTING. ORAL:MAY BE  
HARMFUL IF INGESTED. CHRONIC- UNKNOWN.

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT WITH REAGENTS, RINSE WELL WITH WATER. IN  
  
CASE OF INHALATION, REMOVE TO FRESH AIR. EYE: FOR ALL KIT  
COMPONENTS, FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.  
SEEK MEDICAL ATTENTION. SKIN: FLUSH WITH LARGE AMOUNTS OF WATER.  
USE SOAP AND WATER TO WASH AWAY ORGANIC COMPONENTS. INHALATION: IN  
CASE OF INHALATION, REMOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:=57.2C, 135.F  
Extinguishing Media:DO NOT USE WATER ON A SODIUM FIRE, DRY CHEMICAL,  
FOAM, CO2.  
Fire Fighting Procedures:DO NOT USE WATER. WEAR SCBA. AVOID BREATHING  
SODIUM OXIDE FUMES THAT WILL FORM ON COMBUSTION.  
Unusual Fire/Explosion Hazard:SODIUM WILL FORM HYDROGEN AND SODIUM  
OXIDE WHEN MOISTURE IS PRESENT. DIGLYME MAY FORM PEROXIDES ON  
EXPOSURE TO AIR

===== Accidental Release Measures =====

Spill Release Procedures:AMPULE 2: NAPHTHALENE/DIGLYME AMPULE ABSORB  
COMPLETELY AND DISPOSE OF AS ORGANIC WASTE.

===== Handling and

Storage =====

Handling and Storage Precautions:STORE TEST KITS IN COOL, DRY PLACE.  
CHECK EXPIRATION DATE PRIOR TO PERFORMING TEST.

Other Precautions:TEST TUBE 2; DISPOSE OF IN ACCORDANCE WITH ALL  
APPLICABLE FEDERAL, STATE AND LOCAL GOVERNMENT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED DURING NORMAL USE.

Ventilation:PERFORM TEST ONLY IN WELL-VENTILATED AREA.

Protective Gloves:RUBBER TO PERFORM CLOR-N-OIL TEST;  
VITON FOR PCBs.

Eye Protection:SAFETY GLASSES

Other Protective Equipment:WEAR APPROPRIATE SAFETY EQUIPMENT  
(ELECTRICAL) WHEN PERFORMING THE TEST ON SITE.

Supplemental Safety and Health

FROM PROD ID: KIT FOR DEXSIL CLOR-N-OIL 20, 50, 100 OR 500 PCB

SCREENING KIT CONTAINING: AMPULE 1(GRAY), AMPULE 2 (BLUE-DOT),  
AMPULE 3, AMPULE 4 (RED-GREEN), AMPULE 5 (COLORLESS); AQUEOUS  
SOLN.THIS IS A PART OF 6 PART KIT, MSDS #S;  
CLMSG,CLMSM,CLMSJ,CLMSK,CLMSL.

===== Physical

and Chemical Properties =====

HCC:F2

Boiling Pt.=168.C, 334.4F

Vapor Pres:1.7

Spec Gravity:0.95

Evaporation Rate & Reference:0.36 (BUAC=1)

Solubility in Water:75%

Appearance and Odor:COLORLESS; ETHER -LIKE ODOR

Percent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:MOISTURE

Hazardous Decomposition Products:SODIUM WILL FORM HYDROGEN AND SODIUM

OXIDE WHEN MOISTURE IS PRESENT. DIGLYME MAY FORM PEROXIDES ON EXPOSURE TO AIR. OTHER SOLUTIONS ARE STABLE.

Conditions to Avoid Polymerization:MOISTURE WITH SODIUM AMPULE.

===== Disposal Considerations =====

Waste Disposal Methods:PIPETTE: MAY CONTAIN RESIDUAL PCBS, DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGUALTIONS. TEST TUBE 1: CONTENTS INCLUDE REACTED OIL SAMPLE AND ORGANIC LIQUID , AND MAY CONTA IN RESIDUAL PCBS.

DISPOSE OF AS ORGANIC WASTE IN ACCORDANCE WITH ALL APPLICABLE FEDER AL, STATE AND LOCAL REGULATIONS. SEE PREC

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all l

iability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.