

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- CA8200B DESO HS  
ACTIVATOR -- 8010-01-441-6014

===== Product Identification =====

Product ID:CA8200B DESO HS ACTIVATOR

MSDS Date:02/08/1999

FSC:8010

NIIN:01-441-6014

Status Code:A

MSDS Number: CLMYM

=== Responsible Party ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLEN

DALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:METHYL AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000

= Wt:10.

OSHA PEL:465 MG/M3;100 PPM

ACGIH TLV:233 MG/M3;50 PPM

Ingred Name:HOMOPOLYMER OF HDI

CAS:28182-81-2

Code:F

RTECS #:NQ9170000

= Wt:80.

Ingred Name:AROMATIC SOLVENT (PETROLEUM)

CAS:64742-94-5

Code:F

RTECS #:WF3100000

&lt; Wt:5.

ACGIH TLV:100 PPM

Ingred Name:1,2,4-TRIMETHYLBENZENE

CAS:95-63-6

RTECS #:DC3325000

&lt; Wt:5.

OSHA PEL:25 PPM

ACGIH TLV:25 PPM

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

&lt; Wt:5.

OSHA PEL:710 MG/M3;150 PPM

ACGIH TLV:713 MG/M3

;150 PPM

ACGIH STEL:950 MG/M3;200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYES: MAY CAUSE BURNING, TEARING AND REDDENING. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN. POSSIBLE DERMATITIS. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS AND FATIGUE. INGESTION : MAY CAUSE DROWSINESS, DIZZINESS AND NAUS

EA.

Effects of Overexposure: EYES: VAPOR OR LIQUID CAN IRRITATE THE EYES.  
SKIN: CONTACT WITH LIQUID MAY CAUSE INFLAMMATION AND EVENTUAL  
BLISTERING OF THE SKIN IF THE CONTACT IS PROLONGED. INHALATION:  
VAPOR CAN CAUSE IRRITATION OF THE NOSE AND THROAT AT ABOUT 200  
PPM. MAY CAUSE DROWSINESS, DIZZINESS. SLIGHT INCOORDINATION AND  
UNCONSCIOUSNESS. INGESTION: CAN CAUSE A BURNING SENSATION IN THE  
MOUTH AND STOMACH, NAUSEA, VOMITING AND SALIVATION. VOMITING OF  
BLOOD, CHEST PAIN, COUGH AND HOARSENESS HAVE ALSO BEEN DESCRIBED.

=====  
===== First Aid Measures =====

First Aid: FLUSH WITH WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT  
A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. DO NOT USE SOLVENTS.  
REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. IF SYMPTOMS  
PERSIST, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR  
FROM EXPOSURE. GIVE ARTIFICIAL RESPIRATION OR CARDIOPULMONARY  
RESUSCITATION (CPR) IF BREATHING  
IS DIFFICULT, GET MEDICAL  
ATTENTION. INGESTION: GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method: SCC  
Flash Point: =38.9C, 102.F  
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM.  
Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE. COOL FIRE  
EXPOSED CONTAINERS WITH WATER. FOG NOZZLES ARE PREFERRED. WEAR  
NIOSH/MSHA APPROVED SELF CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING TO PREVENT CONTACT WITH  
SKIN AND EYES.  
Unusual Fire/Explosion Hazard: VAPORS MAY ACCUMULATE IN INADEQUATELY  
VENTILATED OR CONFINED AREAS. VAPORS MAY FORM EXPLOSIVE MIXTURES  
WITH AIR. VAPORS MAY TRAVEL LONG DISTANCES. FLASHBACK OR FLAME TO  
THE HANDLING SITE MAY OCCUR. CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT.

=====  
===== Accidental Release Measures =====

Spill Release Procedures: PROTECT FROM IGNITION. WEAR AIR-SUPPLIED  
RESPIRATOR FOR UNVENTILATED SPILL. CO

VER WITH ABSORBENT MATERIAL  
AND SCOOP INTO CONTAINER. CLEAN RESIDUE WITH A SUITABLE SOLVENT.  
CERCLA RQ FOR N-BUTYL ACETATE IS 5,000 LBS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE  
FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. DO NOT STORE  
ABOVE 120 DEG F.

Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT,  
PUNCTURE OR WELD ON OR NEAR DRUM. VAPORS OF THI  
S PRODUCT ARE  
HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES  
LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS  
OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW TLV AND PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:GOGGLES OR  
FULL FACE SHIELD.

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER  
PROTECTIVE CLOTHING. SAFETY SHOWER, EYE BATH ANS WASHING FACILITIES  
SHOULD BE AVAILABLE.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:259-300 DEG F

Vapor Density:HEAVIER

Spec Gravity:1.088

VOC Pounds/Gallon:206

Appearance and Odor:CLEAR LIQUID

Percent Volatiles by Volume:24.6%

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS  
INCLUDING CARBON DIOXIDE AND CARBON MONOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WHEN DISPOSING OF THIS MATERIAL, ENSURE THAT IT  
IS PACKAGED, STORED, TRANSPORTED AND OTHER WISE MANAGED IN  
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

=====

=====  
MSDS Transport Information  
=====

Transport Information:DOT HAZARD CLASS: FLAMMABLE LIQUID, SHIPPING  
NAME: PAINT, HAZARD CLASS 3 PACKING GROUP 3, UN#: UN1263

=====  
Regulatory Information  
=====

SARA Title III Information:SECTION 313: XYLENE AND TOLUENE

Federal Regulatory Information:ALL INGREDIENTS IN THIS PRODUCT ARE  
LISTED IN THE TSCA INVENTORY. MANUFACTURER OF THIS PRODUCT  
RECOMMENDED 50 PPM TWA AND 100 PPM STEL. ON AIRB

ORNE CONTAMINANTS

LIST: AMORPHOUS SILICA AND TITANIUM DIO XIDE, BUT ARE FULLY  
ENCAPSULATED THEREFORE ARE NOT HAZARDOUS UNLESS PRODUCT IS SANDED  
OR GROUND SO AS TO RELEASE. CERCLA RQ XYLENE: 1000 LBS. CERCLA RQ  
TOLUENE: 1000 LBS.

State Regulatory Information:IS KNOWN TO THE STATE OF CALIFORNIA TO  
CAUSE REPRODUCTIVE TOXICITY - TOLUENE

=====  
Other Information  
=====

Disclaimer (provided with this information by the compiling agencies):

T

his information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.