

GOODYEAR TIRE AND RUBBER CO -- PLIOBOND 30 -- 8040-00-764-4424

===== Product Identification =====

Product ID:PLIOBOND 30  
MSDS Date:09/29/1977  
FSC:8040  
NIIN:00-764-4424  
Status Code:A  
MSDS Number: CLNJL  
=== Responsible Party ===  
Company Name:GOODYEAR TIRE AND RUBBER CO  
Address:1144 E MARKET ST  
City:AKRON  
State:OH  
ZIP:44316-0001  
Country:US  
Info Phone Num:330-796-1906/613-996-66669(CANADA)  
Emergency  
Phone Num:216-794-2121  
Preparer's Name:ERNEST CARTER  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:73842

=== Contractor Identification ===  
Company Name:GOODYEAR TIRE AND RUBBER CO  
Address:1144 E MARKET ST  
Box:City:AKRON  
State:OH  
ZIP:44316-0001  
Country:US  
Phone:330-796-1906/613-996-66669(CANADA)  
CAGE:73842

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE  
CAS:78-93-3  
RTECS #:EL6475000  
= Wt:60.  
OSHA PEL:590 MG/M3;200 PPM  
ACGIH TLV:590 MG/M3;200 PPM  
ACGI

H STEL:885 MG/M3;300 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES, NOSE, AND THROAT, HEADACHE,  
NAUSEA, AND NARCOSIS POSSIBLE AT VERY HIGH VAPOR CONCENTRATIONS.

===== First Aid Measures =====

First Aid:IF INHALED, REMOVE TO FRESH AIR. IN CASE OF CONTACT, FLUSH  
EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A  
PHYSICIAN. WAS  
H SKIN WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:=-3.3C, 26.F

Lower Limits:2%

Upper Limits:12%

Extinguishing Media:CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:TREAT AS SOLVENT FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILATION: TAKE PRECAUTIONS  
AGAINST ALL SOURCES OF IGNITION. SCOOP BULK OF MATERIAL INTO  
CONTAINER FOR DI  
SPOSAL. CLEAN UP WITH RAGS AND SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN  
FLAME. USE ONLY WITH ADEQUATE VENTILATION,. AVOID PROLONGED OR  
REPEATED BREATHING OF VAPOR OR SPRAY MIST. AVOID CONTACT WITH SKIN  
AND EYES.

===== Exposure Controls/Personal Protection =====

Ventilation:TO MAINTAIN TLV

Eye Protection:SAFETY GLASSES

Other Protective Equipment:ALL CHEMICA

LS SHOULD BE HANDLED SO AS TO

PREVENT EYE CONTACT AND EXCESSIVE OR REPEATED SKIN CONTACT.

APPROPRIATE EYE AND SKIN PROTECTION SHOULD BE EMPLOYED, INHALATION OF DUSTS AND VAPORS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=80.C, 176.F

Vapor Pres:71 MM HG AT 20 C

Vapor Density:2.5

Spec Gravity:0.89

Solubility in Water:INSOLUBLE

Appearance and Odor:TAN LIQUID, KETONE ODOR,

Percent Volatiles by Volume:60%

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON COMBUSTION PRODUCTS, NITROGEN COMPOUNDS

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR ALLOW SOLVENT TO EVAPORATE AND DISPOSE OF SOLIDS IN LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information i

s formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.