View NSN Online: https://aerobasegroup.com/nsn/6850-00-285-9432

PHOENIX INDUSTRIES INC -- ISOPROPANOL - DOSS WETTING AGENT -- 6850-00-285-9432

======== Product Identification ============

Product ID:ISOPROPANOL - DOSS WETTING AGENT

MSDS Date:09/12/2001

FSC:6850

NIIN:00-285-9432

Status Code:A

MSDS Number: CLNTX

=== Responsible Party ===

Company Name: PHOENIX INDUSTRIES INC Address: 1519 CHAMBERLAYNE PARKWAY

City:RICHMOND

State:VA ZIP:23222 Country:US

Info Phone Num:804-26 4-5183/FAX: 264-5535

Emergency Phone Num:(800) 424-9300 Chemtrec Ind/Phone:(800)424-9300

CAGE:0YED2

=== Contractor Identification ===

Company Name: PHOENIX INDUSTRIES INC Address: 1519 CHAMBERLAYNE PARKWAY

Box:City:RICHMOND

State:VA ZIP:23222 Country:US

Phone:804-264-5183/FAX: 264-5535 Contract Num:SP0450-01-M-ZH52

CAGE:0YED2

======= Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ALCOHOL

CAS:67-63-0

RTECS #:NT8050000

= Wt:75.

OSHA PEL:980 MG/M3;400 PPM

ACGIH T

LV:983 MG/M3;400 PPM ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:DIOCTYL SULFOSUCCINATE SODIUM CAS:577-11-7
RTECS #:WN0525000
= Wt:25.

========= Hazards Identification ==============

LD50 LC50 Mixture:ORAL, RAT, LD50: 5045 MG/KG, ISOPROPANOL
Health Hazards Acute and Chronic:FLAMMABLE LIQUID. HARMFUL IF SWALLOWED
OR INHALED. MAY CAUSE RESPIRATORY IRRITATION AND SKIN IRRITATION.
MAY CAUSE SERIOUS DAMAGE TO EYES. MAY REACT VIOLENTLY WITH STRONG
OXIDIZING AGENTS.

Εf

fects of Overexposure:FLAMMABLE LIQUID. HARMFUL IF SWALLOWED OR INHALED. MAY CAUSE RESPIRATORY IRRITATION AND SKIN IRRITATION. MAY CAUSE SERIOUS DAMAGE TO EYES.

First Aid:SKIN CONTACT: WASH EXPOSED AREA WITH WATER FOR 15 MINUTES. LAUNDER EXPOSED CLOTHING BEFORE REUSE. IF IRRITATION OCCURS OR PERSISTS, GET MEDICAL ATTENTION. EYE CONTACT: FLUSH WATER FOR 15 MINUTES. GE T MEDICAL ATTENTION. INGESTION: INDUCE VOMITING AS

DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET IMMEDIATE MEDICAL ASSISTANCE. SHOW THIS CONTAINER AND LABEL TO MEDICAL PERSONNEL TO HELP IN IDENTIFICATION OF CONTAINER CONTENTS.

=========== Fire Fighting Measures ==============

Flash Point Method:CC Flash Point:=12.C, 53.6F

ISOPROPANOL

Autoignition Temp:=399.C, 750.2F

Lower Limits:2.0 Upper Limits:12.7

Extinguishing Media: WATER SPRAY, DRY CHEMICAL, ALCOH

- OL FOAM, OR CARBON DIOXIDE.
- Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. USE WATER SPRAY TO COOL FIRE EXPOS ED CONTAINERS, DILUTE SPILLS TO NONFLAMMABILE MIXTURES, PROTECT PERSONNEL ATTEMPTING TO STOP LEAK, DISPERSE VAPORS.
- Unusual Fire/Explosion Hazard:ABOVE FLASH POINT, VAPOR-AIR MIXTURES ARE EXPLOSIVE WITHIN FLAMMABLE LIM
- ITS NOTED ABOVE. CONTACT WITH STRONG
 OXIDIZERS MAY CAUSE FIRE OR EXPLOSION. VAPORS CAN FLOW ALONG
 SURFACES TO DISTANT IGNITION S OURCE AND FLASH BACK. SENSITIVE TO
 STATIC DISCHARGE.

======== Accidental Release Measures ===========

- Spill Release Procedures: VENTILATE SPILL AREA. REMOVE SOURCES OF IGNITION. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. ISOLATE HAZARD AREA. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. CONTAIN AND RECOVER LI
- Q UID WHEN POSSIBLE. USE NON-SPARKING TOOLS AND EQUIPMENT. COLLECT LIQUID IN AN APPROPRIATE CONTAINER OR ABSORB WITH AN INERT MATERIAL (E.G., VERMICULITE, DRY SAND, EARTH), AND (CONTD. SEE "OTHER INFO")

- Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE. SEPARATE FROM INCOMPATIBLES. STORAGE AND USE AREAS SHOULD BE NO SMO
- KING AREAS.USE IN WELL-VENTILA TED AREA. WEAR PERSONAL PROTECTION WHERE EXPOSURE IS PRESENT. WEAR APPROPRIATE PROTECTION FOR EYES.
- Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY SINCE THEY RETAIN PRODUCT RESIDUE (VAPORS, LIQUID); OBSERVE ALL WARNINGS AND PRECAUTIONS LISTED FOR THE PRODUCT.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: IN EVENT OF A FIRE, WEAR A NIOSH-APPROVED SELF-CONTAINED BREATHING AP

THE PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. Ventilation:USE IN WELL-VENTILATED AREA. Eye Protection:WEAR APPROPRIATE PROTECTION FOR EYES. Other Protective Equipment:WEAR PERSONAL PROTECTION WHERE EXPOSURE HAZARD IS PRESENT. WEAR APPROPRIATE PROTECTION FOR EYES AS MAY BE REQUIRED TO PROTECT FROM SPLASH OR LIQUID MIST/SPRAY. Supplemental Safety and Health
========= Physical/Chemical Properties =========
HCC:F2 Vapor Pres:44 @25C (77F) Vapor Density:0.82 Spec Gravity:0.82 pH:SLIGHTLY BASIC Solubility in Water:MISCIBLE Appearance and Odor:CLEAR TO LIGHT AMBER LIQUID; ALCOHOLIC ODOR
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES HEAT,FLAME,STRONG OXIDIZERS,ACETALDEHYDE,ACIDS,CHLORINE,ETHYLENE OXIDE,HYDROGEN-PALLADIUM COMBINATION,HYDROGEN PEROXIDE-SULFURIO ACID COMBINATION,POTASSIUM TERT-BUTOXIDE,HYPOCHLOROUS ACID,ISOCYANATES,NITROFO RM,PHOSGENE,ALUM Stability Condition to Avoid:STABLE UNDER ORDINARY CONDITIONS OF USE AND STORAGE. HEAT AND SUNLIGHT CAN CONTRIBUTE TO INSTABILITY. AVOID HEAT, FLAMES, IGNITION SOURCES AND INCOMPATIBLES. Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE MAY FORM WHEN HEATED TO DECOMPOSITION. Conditions to Avoid Polymerization:WILL NOT OCCUR.
========= Toxicological Information ==========
Toxicological Information:ISOPROPYL ALCOHOL (CAS # 67-63-0): ORAL, RAT, LD50: 5045 MG/KG; SKIN, RABBIT, LD50: 12.8 GM/KG; INHALATION, RAT, LC50: 16,000 PPM/8-HR; INVESTIGATED AS A TUMORIGEN, MUTAGEN, REPRODUCTIVE EFFECTOR. DIO CTYL SODIUM SULFOSUCCINATE (CAS # 577-11-7): ORAL, RAT, LD50: 1900 MG/KG.
========== MSDS Transport Information ====================================
Transport Information:DOT CLASSIFICATION: FLAMMABLE LIQUID N.O.S.; CLASS: 3; UN 1993; PKG: I I.
============ Other Information ====================================

PARATUS WITH FULL FACEPIECE OPERATED IN

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situat ion.