

TRUETECH INC -- AMPOULE ASSEMBLY, MEOH/W, MEOH-T, MEOH-P (SEE SUPPL) --
6665-01-293-2149

===== Product Identification =====

Product ID:AMPOULE ASSEMBLY, MEOH/W, MEOH-T, MEOH-P (SEE SUPPL)

MSDS Date:02/01/1996

FSC:6665

NIIN:01-293-2149

Status Code:A

Kit Part:Y

MSDS Number: CLPKN

=== Responsible Party ===

Company Name:TRUETECH INC

Address:680 ELTON AVE

City:RIVERHEAD

State:NY

ZIP:11901-2555

Country

:US

Info Phone Num:516-727-8600

Emergency Phone Num:516-727-8600

CAGE:06421

=== Contractor Identification ===

Company Name:TRUETECH INC

Address:680 ELTON AVE

Box:City:RIVERHEAD

State:NY

ZIP:11901-2555

Country:US

Phone:516-727-8600

CAGE:06421

===== Composition/Information on Ingredients =====

Ingred Name:METHANOL

CAS:67-56-1

RTECS #:PC1400000

OSHA PEL:200 PPM

ACGIH TLV:200 PPM

ACGIH STEL:328 MG/M3;250 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazard

s Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:IF VAPOR CONCENTRATION EXCEEDS PEL:
ACUTE: HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, VOMITING.
Effects of Overexposure:IF VAPOR CONCENTRATION EXCEEDS PEL: ACUTE:
HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, VOMITING.

===== First Aid Measures =====

First Aid:SWALLOWING: GIVE TWO GLASSES OF WATER AND INDUCE V
OMITING.
INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE
OXYGEN. SKIN OR EYES: FLUSH WITH WATER.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:=52.C, 125.6F
Lower Limits:6.0%
Upper Limits:36.0%
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL POWDER, ALCOHOL OR
POLYMER FOAM
Fire Fighting Procedures:NONE REQUIRED
Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL AND IGNITE FAR FROM
SOURCE.

===== =
= Accidental Release Measures =====

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. COLLECT
FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT BREATHE VAPORS. USE WITH
ADEQUATE VENTILATION. DO NOT GET INTO EYES, ON SKIN, OR ON
CLOTHING. KEEP AWAY FROM HEAT AND OPEN FLAME.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protecti

on:NONE
Ventilation:MECHANICAL.
Protective Gloves:RUBBER OR PLASTIC.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:EYEBATH OR SAFETY SHOWER.
Work Hygienic Practices:ACCIDENTAL CONTACT SHOULD BE WASHED AWAY IMMEDIATELY.

Supplemental Safety and Health
ITEM IS A FIVE PART KIT. THIS ITEM IS A COMPONENT OF M256A1 DETECTOR KIT AND SIMULATOR, DETECTOR KIT, TRAINING M256A1. SEE MSDS SERIAL #CLPKP, CLPKQ, CLPKR AND CLPKS.

===== Physical/Chemical Properties =====
=====

HCC:F2
Boiling Pt:=64.8C, 148.6F
Vapor Pres:96@20C
Vapor Density:1.11
Spec Gravity:1 (BUAC=1)
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR LIQUID; ALCOHOL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, IGNITION SOURCES
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:BURNING OR HEAT CAN PRODUCE CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====
=====

Waste Disposal Methods:INCINERATE IN A FURNACE WHERE PERMITTED UNDER FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek

competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.