

FARWEST PAINT MANUFACTURING CO -- QUICK DRY GLOSS ENAMEL COLOR: #17886 WHITE --
8010-00-598-7214

===== Product Identification =====

Product ID:QUICK DRY GLOSS ENAMEL COLOR: #17886 WHITE

MSDS Date:06/01/1993

FSC:8010

NIIN:00-598-7214

Status Code:A

MSDS Number: CLPTK

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Coun

try:US

Info Phone Num:206-244-8844

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

Code:F

RTECS #:WJ8925000

= Wt:39.

OSHA PEL:2900 MG/M3;500 PPM

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO KNOWN

CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY ACGIH, OSHA,
NTP, IARC.

Effects of Overexposure:SKIN: THIS MATERIAL MAY CAUSE

IRRITATION.SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR
REPEATED CONTACT. I

INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY

MIST CAN RESULT IN HEADACHE, DIZZINESS, NAUSEA AND LOSS OF
CONSCIOUSNESS.SOME REPORTS HAVE ASSOCIATED REPEATED & PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN &
NERVOUS SYSTEM DAMAGE. EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.

=====
===== First Aid Measures =====
=====

First Aid:SKIN: WASH WITH SOAP AND WATER.REMOVE AND WASH ANY
CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLU

SH WITH LARGE

QUANTITIES OF WATER FOR 15 MINUTES AND SEEK MEDICAL

ATTENTION.SWALLOWING: IF INGESTED DO NOT INDUCE VOMITING; KEEP

PERSON WARM AND QUIET AND GET MEDICAL ATTENTION. INHALATION: REMOVE

VICTIM TO FRESH AIR IMMEDIATELY. IF RESPIRATORY SYMPTOMS DEVELOP,
SEEK MEDICAL ATTENTION AT ONCE.

=====
===== Fire Fighting Measures =====
=====

Flash Point:=-41.7C, 107.F

Lower Limits:0.7%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG.

Fire Fight

ing Procedures:FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR

PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING

APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONNEL.WEAR PROTECTIVE
CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN

AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED

CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:REM

REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE MATERIAL INTO A CLOSED CONTAINER. IF LARGE SPILL, DIKE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATER SYSTEMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP.

=====
===== Handling and Storage =====

Handling and Storage Precautions: AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR SPRAY MIST. KEEP A WAY FROM HEAT OR OPEN FLAME.

THIS MATERIAL MAY CAUSE SENSITIZATION. DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD. KEEP CONTAINERS CLOSED WHEN NOT IN USE.,

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MIST WHEN THE TLV OR PEL IS EXCEEDED.

Ventilation: GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL

VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVEL BELOW THE LIMITS LISTED OF

Protective Gloves: PROTECTIVE GLOVES: Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

Work Hygienic Practices: WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 307-389 F

Vapor Pres: 2.6

Vapor Density: HEAVIER

VOC Pounds/Gallon: 437

VOC Grams/Liter: 9.5

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: NIL

Appearance and Odor: WHITE OILY LIQUID, MILD ODOR

Percent Volatiles by Volume: 55%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: HEAT, SPARKS AND O

PEN FLAME.

Hazardous Decomposition Products:COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF THIS MATERIAL OR ITS CONTAINERS REQUIRES COMPLIANCE WITH APPLICABLE LABELING, PACKAGING AND RECORDKEEPING STANDARDS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by

elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.