

STIC-ADHESIVE PRODUCTS CO INC -- ENAMEL, INTERIOR, NONFLAMING (DRY), CHLORINATED
ALKYD RESIN, -- 8010-01-344-5087

===== Product Identification =====

Product ID:ENAMEL, INTERIOR, NONFLAMING (DRY), CHLORINATED ALKYD RESIN,

MSDS Date:08/01/2000

FSC:8010

NIIN:01-344-5087

Status Code:A

MSDS Number: CLPYH

=== Responsible Party ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

City:L

OS ANGELES

State:CA

ZIP:90063-1675

Country:US

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:1BH90

=== Contractor Identification ===

Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST

Box:City:LOS ANGELES

State:CA

ZIP:90063-1675

Country:US

CAGE:1BH90

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

= Wt:21.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:ZINC PHOSPHATE
= Wt:16.

Ingred Name:BARIUM METABORATE
= Wt:15.

Ingred Name:POLYMER BASE
= Wt:35.

Ingred Name:RESIN SOLUTION

Ingred Name:PAINT THINNER
CAS:8052-41-3
Code:F
RTECS #:WJ8925000
= Wt:9.
OSHA PEL:2900 MG/M3;500 PPM
ACGIH TLV:525 MG/M3;100 PPM

Ingred Name:DRIERS
CAS:136-52-7
Code:F
= Wt:3.

Ingred Name:LEVELING AGENT ANTISKING AGENT THIXATROPIC AGENT
= Wt:1.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES
Ingestion:YES

Health Hazards Acute and Chronic:INGESTION: KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION. EYE CONTACT: CAUSES SEVERE EYE IRRITATION. SKIN CONTACT: CAUSES PRIMARY SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. INHA LATION: VAPOR AND SPRAY MIST HARMFUL IF INHALED. VAPOR IRRITATES EYES, NOSE, AND THROAT. MAY IRRITATE LUNGS. REPEATED EXPOSURE TO HIGH VAPOR CONCENTRATIONS MAY CAUSE IRRITATION OF THE RESPIRATORY SYST EM AND PERMANENT BRAIN AN

D
NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

Effects of Overexposure:EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, AND LOSS OF COORDINATION ARE INDICATION THAT SOLVENT LEVELS ARE TOO HIGH. REDNESS, ITCHING, BURNING SENSATION AND VISUAL DISTURBANCES MAY INDICATE EXCESSIVE EYE CONTACT. DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE CONDITIONS ASSOCIATED WITH EXCESSIVE SKIN CON

TACT. CHRONIC EXPOSURE: AVOID LONG TERM AND
REPEATED CONTACT. PRODUCT CONTAINS TITANIUM DIOXIDE.

===== First Aid Measures =====

First Aid:INGESTION: IF SWALLOWED, GIVE 1 OR 2 GLASSES OF WATER, BUT DO
NOT INDUCE VOMITING.EYE CONTACT: FLUSH EYES IMMEDIATELY WITH PLENTY
OF WATER FOR AT LEAST 15 MINUTES. SKIN CONTACT: FLUSH IMMEDIATELY
WITH PLENTY OF WATER FOLLOWED BY WASHING WITH SOAP AND WATER.
INHALATION: IF AFFECTED BY INHALATION OF V
APOR OR SPRAY MIST,
REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION AND OTHER
SUPPORTIVE MEASURES AS REQUIRED. CONTACT POISON CONTROL CENTER
IMMEDIATELY IF INGESTED.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-40.6C, 105.F

Extinguishing Media:NFPA CLASS B EXTINGUISHERS, CARBON DIOXIDE, DRY
CHEMICAL, OR UNIVERSAL AQUEOUS FILM FORMING FOAM.

Fire Fighting Procedures:WATER SPRAY MAY BE USED TO COOL CLOSED
CONTAINER

S TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION
OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG
NOZZLES ARE PREFERABLE. FIRE F IGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE
FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. CLOSED
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY
ON HOT SURFACES. TOXIC GASES MAY FORM WHEN PRODUCT IS CONTACTED
BY
FLAME OR HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE MAXIMUM VENTILATION. PERSONNEL MUST
HAVE PROPER RESPIRATORY EQUIPMENT. REMOVE ALL SOURCES OF IGNITION.
TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE, OR OTHER
ABSORBENT MATERIAL AND PLA CE INTO CONTAINERS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLING AND STORAGE PRECA

UTIONS:

STORE LARGE QUANTITIES IN BUILDING DESIGNED AND PROTECTED FOR STORAGE. DO NOT STORE ABOVE 120 DEG F.

Other Precautions:IF THIS MATERIAL IS PART OF A MULTIPLE COMPONENT SYSTEM, READ THE MATERIAL SAFETY DATA SHEET(S) FOR THE OTHER COMPONENTS BEFORE BLENDING THE RESULTANT MIXTURE MAY HAVE THE HAZARDS OF ALL ITS PARTS. CO NTAINERS SHOULD BE GROUNDED BEFORE POURING. AVOID FREE FALL OF LIQUIDS IN EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protect ion =====

Respiratory Protection:OVEREXPOSURE CAN BE PREVENTED WITH PROPER VENTILATION. (NIOSH/MSHA APPROVED 9TC-23C) AIR PUFIFYING OR AIR SUPPLIED (TC-19C) RESPIRATORS MAY ALSO REDUCE EXPOSURE. READ RESPIRATOR MANUFACTURER'S INSTRUC TIONS AND LITERATURE CAREFULLY TO DETERMINE THE TYPE OF AIRBORNE CONTAMINANTS AGAINST WHICH THE RESPIRATOR IS INEFFECTIVE AND HOW IT IS TO BE PROPERLY FITTED.

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION.

Protectiv

e Gloves:WEAR IMPERMEABLE NITRILE RUBBER OR NEOPRENE RUBBER.

OTHER EQUIPMENT:Eye Protection:WEAR CHEMICAL. TYPE SPLASH GOGGLES OR FULL FACE SHIELD.

Other Protective Equipment:CLEAN OR DISCARD CONTAMINATED CLOTHING AND SHOES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:>154.4C, 310.F

B.P. Text:310-390 F AT 760 MM HG

Vapor Pres:2.000 MMHG AT 68 F

Vapor Density:4.9

Spec Gravity:1.62-1.65

VOC Pounds/Gallon:340

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG ALKALIS, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID CONTACT WITH STRONG ALKALIS, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL STATE, PROVINCIAL, AND LOCAL

ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.