

SPECIALTY TONER CORP -- 8612-6M, MAGENTA TONER CONCENTRATE -- 6750-01-474-2993

===== Product Identification =====

Product ID:8612-6M, MAGENTA TONER CONCENTRATE

MSDS Date:01/01/2001

FSC:6750

NIIN:01-474-2993

Status Code:A

Kit Part:Y

MSDS Number: CLQDK

=== Responsible Party ===

Company Name:SPECIALTY TONER CORP

Address:19 INDUSTRIAL ROAD

City:FAIRFIELD

State:NJ

ZIP:07004

Country:US

Info Phone Num:97

3-575-3643/ (973) 575-9626 FAX

Emergency Phone Num:(202) 483-7616

Chemtrec Ind/Phone:(800)424-9300

CAGE:1PVH2

=== Contractor Identification ===

Company Name:SPECIALTY TONER CORP

Address:19 INDUSTRIAL ROAD

Box:City:FAIRFIELD

State:NJ

ZIP:07004

Country:US

Phone:973-575-3643/ (973) 575-9626 FAX

CAGE:1PVH2

===== Composition/Information on Ingredients =====

Ingred Name:POLYMER/RESIN NJTSRN# 222760362-5014

Ingred Name:POLYMER/RESIN NJTSRN# 222760362-5015

ACGIH TLV:NONE ESTABLISHED

Ingred Name:(PIGMENT) RED NJTSRN# 222760362-5005  
&lt; Wt:6.

Ingred Name:ISOPARAFFINIC PETROLEUM SOLVENT  
CAS:64742-48-9  
= Wt:84.  
ACGIH TLV:300 PPM

Ingred Name:POLYMER/RESIN NJSRN# 222760362-5013  
&lt; Wt:9.  
ACGIH TLV:NONE

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE: IRRITANT TO EYE - MAY CAUSE  
CONJUNCTIVITIS. SKIN: PROLONGED CONTACT CAUSES DEFATTING, DRYING,  
CRACKING DER  
MATITIS. INHALATION: NOT NORMALLY AN INHALATION HAZARD,  
OVEREXPOSURE MAY CAUSE HEADACHE, NAUSEA AND RESPIRATORY  
IRRITATION. INGESTION: NAUSEA AND POSSIBLE GASTRO-INTESTINAL  
IRRITATION. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.  
Effects of Overexposure:EYE: IRRITANT TO EYE - MAY CAUSE  
CONJUNCTIVITIS. SKIN: PROLONGED CONTACT CAUSES DEFATTING, DRYING,  
CRACKING DERMATITIS. INHALATION: NOT NORMALLY AN INHALATION HAZARD,  
OVEREXPOSURE MAY CAUSE HEADACHE, NAUSEA AND RESPIRA  
TORY  
IRRITATION. INGESTION: NAUSEA AND POSSIBLE GASTRO-INTESTINAL  
IRRITATION. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.  
Medical Cond Aggravated by Exposure:DERMATITIS. REPEATED INHALATION  
EXPOSURE TO RATE OF A SIMILAR HYDROCARBON AT CONCENTRATIONS GREATER  
THAN OR EQUAL TO 300PPM IN AIR CAUSED LOW GRADE (MILD) ANEMIA AND  
KIDNEY EFFECTS.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH LARGE AMOUNTS OF WATER, INCLUDING UNDER  
EYELIDS. SKIN: WASH WITH SOAP AND WATER. REMOVE ANY CONTAMINATED  
CLOTHING. INHALATION: MOVE TO FRESH AIR; IF BREATHING DIFFICULTY,  
ADMINISTER OX YGEN AND GET MEDICAL HELP. INGESTION: DO NOT INDUCE  
VOMITING DUE TO ASPIRATION HAZARD. CALL A PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:103-106F  
Autoignition Temp:=293.3C, 560.F  
Autoignition Temp Text:APPROX  
Lower Limits:0.8  
Upper Limits:7.0  
Extinguishing Media:FO

AM, DRY CHEMICAL, CO2, WATER FOG.

Fire Fighting Procedures:AVOID WATER, IT TENDS TO SPREAD HYDROCARBON FIRES.

Unusual Fire/Explosion Hazard:(NFPA) HEALTH 1, FLAMMABILITY 2, REACTIVITY 0, RECOMMENDED BY EXXON.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. COLLECT ON INERT ABSORBENT MATERIAL. PLACE IN WASTE CONTAINER APPROVED FOR COMBUSTIBLE WASTE.

===== Handling and Storage =====  
=====

Handling and Storage Precautions:STORE IN CLOSED, COOL, WELL-VENTILATED AREA AWAY FROM HEAT AND FLAME.

Other Precautions:READ AND FOLLOW LABEL PRECAUTIONS. DO NOT REUSE CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED.

Ventilation:LOCAL EXHAUST: TO MAINTAIN BELOW TLV.

Protective Gloves:LATEX GLOVES FOR OVEREXPOSURE.

Eye Protection:GOGGLES FOR POSSIBLE SPLASHING.

Other Protective Equipment:AN EYEWASH STATION IS DESIRABLE IF SPLASHING IS A POSSIBILITY.

Supplemental Safety and Health

ITEM IS PART OF A KIT. SEE MSDS SERIAL# CLQDW,CLQDV, CLQDT, CLQDS, CLQDR, CLQDQ, CLQDP, CLQDN, CLQDM, CLQDL, CLQDX, AND CLQDJ.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:160-180C

Vapor Pres:1 MM @68F

Vapor Density:5

Spec Gravity:0.76

Evaporation Rate & Reference:.25 - .45

Solubility in Water:IMMISCIBLE

Appearance and Odor:RED/SLIGHT.

===== Stabi

lity and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
VERY STRONG OXIDANTS LIKE CHROMIC ACID OR LIQUID CHLORINE.  
Stability Condition to Avoid: NONE  
Hazardous Decomposition Products: NONE  
Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information: (THIS MATERIAL HAS BEEN EXTENSIVELY TESTED.  
WHEN USED AS INTENDED, IT DOES NOT REPRESENT ANY KNOWN HEALTH OR  
SAFETY HAZARD.) OR  
AL LD50: 5 G/KG(RAT) \*INFORMATION SUPPLIED BY  
EXXON. \*RECOMMENDED EXPOSURE LIMIT 300PPM FOR SOLVENT MANUFACTURED  
BY EXXON. DERMAL LD50: 3.16 G/KG(RABBIT). INHALATION LD50: N/A.  
TLV: N/A. PEL: N/A. VOLATILE N/A (WGT.) 80-100%.

===== Ecological Information =====

Ecological: AQUATIC LD50: N/A.

===== Disposal Considerations =====

Waste Disposal Methods: TREAT AS HAZARDOUS WASTE AND DISPOSE IN  
ACCORDANCE WITH LOCAL ENVIRONMENTAL REGULATIONS. DO NOT POUR DOWN  
COMMON DRAIN.

===== MSDS Transport Information =====

Transport Information: IMDG (I.E. OCEAN) PROPER SHIPPING NAME: PETROLEUM  
DISTILLATES, N.O.S. (CONTAINS ALIPHATIC HYDROCARBON LIQUID, RESIN  
PIGMENT). FLAMMABLE LIQUID, HAZARD CLASSIFICATION: 3.3 ID NUMBER:  
UN1268. PACKING GROUP III, IMDG PAGE #3375. IATA PROPER SHIPPING  
NAME: PETROLEUM DISTILLATE, N.O.S., CONTAINS ALIPHATIC HYDROCARBON  
LIQUID, RESIN, PIGMENT). FLAMMABLE LIQUID, HAZARD CLASSIFICATION: 3  
ID NUMBER: UN1268. PACKING GROUP III. DOT PROPER SHIPPING NAME:  
COMBUSTIBLE LIQUID, N.O.S., (CONTAINS ALIPHATIC HYDROCARBON LIQUID,  
RESIN, PIGMENT), NA 1993, PG III HAZARD CLASSIFICATION: COMB.  
LIQUID.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.