

QPL INC -- SLYDE II LUBRICATING COMPOUND -- 9150-00-823-7860

===== Product Identification =====

Product ID:SLYDE II LUBRICATING COMPOUND

MSDS Date:04/01/1993

FSC:9150

NIIN:00-823-7860

Status Code:A

MSDS Number: CLQJL

=== Responsible Party ===

Company Name:QPL INC

Address:800 N ACADIA RD

City:THIBODAUX

State:LA

ZIP:70301

Country:US

Info Phone Num:504-449-0660

Emergency Phone Num:504 449-0660

CAGE:

KO854

=== Contractor Identification ===

Company Name:QPL INC

Address:800 N ACADIA RD

Box:City:THIBODAUX

State:LA

ZIP:70301

Country:US

Phone:504-449-0660

CAGE:KO854

===== Composition/Information on Ingredients =====

Ingred Name:TRICHLOROTRIFLUOROETHANE

CAS:26523-64-8

= Wt:37.

ACGIH TLV:1000

Ingred Name:METHYL CHLOROFORM

CAS:79-22-1

RTECS #:FG3675000

= Wt:35.

ACGIH TLV:350

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HYDROCARBON PROPELLANT

= Wt:20.

=====

==== Hazards Identification =====

Effects of Overexposure:HEADACHE, DIZZINESS AND NAUSEA.

==== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN. EYE CONTACT: WASH WITH PLENTY OF WATER FOR 15 MIN UTES. SKIN CONTACT: FLUSH WITH WATER.

==== Fire Fighting Measures =====

Lower Limits:6.2

Upper Limits:17.2

Extinguishing Media:MECHANICAL FORM, DRY CHEMICAL, WATER, CO2.

Fire Fighting Procedures:SELF CONTAINED RESPIRATORY EQUIPMENT.

Unusual Fire/Explosion Hazard:NONE

==== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: MOP. WIPE OR SOAK UP WITH ABSORBENT MATERIAL USING PROPER PROTECTIVE EQUIPMENT. LARGE SPILL: FLUSH SPILL TO GROUND AND LET EVAPORATE.

==== Handling and Storage =====

ge =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.

Other Precautions:AVOID BREATHING OF VAPORS. USE ADEQUATE VENTILATION.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:IF CONCENTRATION WILL EXCEED TLV USE SELF CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED.

Protective Gloves:NEOPRENE GLOVES.

Eye Protection:GOGGLES.

Other Protective Equipment:RUBBER A

PRON TO AVOID WETTING CLOTHES.

Work Hygienic Practices:READ INSTRUCTIONS CAREFULLY BEFORE USING. KEEP AWAY FROM CHILDREN.

Supplemental Safety and Health

PRODUCT: SLYDE II. LUBRICATING COMPOUND.

===== Physical/Chemical Properties =====

HCC:V2

Evaporation Rate & Reference:1.2

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AEROSOL WITH HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo

id:YES

NONE

Stability Condition to Avoid:OPEN FLAME OR WELDING ARCS.

Hazardous Decomposition Products:EXPOSURE TO HIGH TEMPERATURES OR OPEN FLAME GENERATED HYDROCARBON AND SMALL AMOUNT OF CHLORINE & PHOSGENE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE OR PUNCTURE CAN, WRAP CONTAINER AND DISPOSE OF IN TRASH COLLECTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.