View NSN Online: https://aerobasegroup.de/nsn/7510-01-448-5157

## SIEKO EPSON CORPORATION HIROOKA OFFICE -- INK CARTRIDGE S020097 -- 7510-01-448-5157

Product ID: INK CARTRIDGE S020097

MSDS Date:06/03/1996

FSC:7510

NIIN:01-448-5157 Status Code:A

MSDS Number: CLQNJ === Responsible Party ===

Company Name: SIEKO EPSON CORPORATION HIROOKA OFFICE

Address:80 HARASHINDEN HIROOKA City:SHIOJIRI-SHI NAGANO-KEN

ZIP:39907

Info Phone Num:+81-2

63-52-2552

Emergency Phone Num:800-424-9300 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:UO569

=== Contractor Identification ===

Company Name: SIEKO EPSON CORPORATION HIROOKA OFFICE

Address:80 HARASHINDEN HIROOKA Box:City:SHIOJIRI-SHI NAGANO-KEN

ZIP:39907

Phone:+81-263-52-2552

CAGE:UO569

======= Composition/Information on Ingredients ========

Ingred Name:WATER Minumum % Wt:68. Maxumum % Wt:73.

Ingred Name:GLYCOLS Minumum % Wt:26. Maxumum % Wt:29.

**Ingred Nam** 

Maxumum % Wt:5.
Ingred Name:DYE-DISSOLUTION-SOLVENT Minumum % Wt:0. Maxumum % Wt:2.
======================================
First Aid:EYE: FLUSH THOROUGHLY WITH WATER. SKIN: WASH WITH SOAP AND WATER
======================================
Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE.
======================================
Spill Release Procedures:IF SPLIT, USE SPONGE TO WIPE UP THE INK. PLACE IT IN CLOSED CONTAINER FOR PROPER DISPOSAL.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE. WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WHEN LARGE NUMBERS OF CELLS ARE INVOLVED IN A FIRE. Ventilation:ADEQUATE Protective Gloves:RUBBER FOR LEAKERS Eye Protection :GOGGLES FOR LEAKERS Other Protective Equipment:EYE BATH, WASHING FACILITIES Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING OR DRINKING.
Supplemental Safety and Health
======================================
Vapor Density:1.06 pH:9~10
Viscosity:3.0 MPA'S AT 20 C Appearance and Odor:YELLOW, MAGENTA AND CYAN LIQUID
========= Stability and Reactivity Data =======

e:DYE STUFF Minumum % Wt:2. ======

Stability Indicator/Materials to Avoid:YES Conditions to Avoid Polymerization:WILL NOT OCCUR.
======== Disposal Considerations ===========
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.
========= MSDS Transport Information ==========

Transport Information:THESE BATTERIES ARE EXCEPTED FROM REGULATIONS AS EACH BATTERY/CELL CONTAIN ABOUT 0.3 GRAM OF LITHIUM, PROVIDED THEY MEET THE REQUIR EMENTS OF 49 CFR 173.185 (B).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informati on to their particular situation.