

DEXTER CORP THE HYSOL DIV -- EPK 0151 PART A, AA0151 -- 8040-00-061-8303

=====
Product Identification
=====

Product ID:EPK 0151 PART A, AA0151
MSDS Date:11/08/1999
FSC:8040
NIIN:00-061-8303
Status Code:A
MSDS Number: CLQSV
=== Responsible Party ===
Company Name:DEXTER CORP THE HYSOL DIV
Address:1 DEXTER DR
City:SEABROOK
State:NH
ZIP:03874
Country:US
Info Phone Num:603-474-5541
Emergency Phone Num
:1-800-424-9300
Preparer's Name:ERNEST CARTER
Chemtrec Ind/Phone:(800)424-9300
CAGE:1JB33

==== Contractor Identification ====
Company Name:DEXTER CORP THE HYSOL DIV
Address:1 DEXTER DR
Box:City:SEABROOK
State:NH
ZIP:03874
Country:US
Phone:603-474-5541/FAX: 603-474-5545
CAGE:1JB33

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN
CAS:25068-38-6
Code:F
RTECS #:CE6880000
Minimum % Wt:60.
Maximum % Wt:100.

Ingred Name:02-1,2-EPOXY-3-BUTOXY
CAS:2426-08-6
Co

de:F
RTECS #:TX4200000
= Wt:8.91
OSHA PEL:270 MG/M3;50 PPM
ACGIH TLV:133 MG/M3;25 PPM

===== Hazards Identification =====

Effects of Overexposure:EYES: MAY CAUSE PAIN, MAY CAUSE SEVERE IRRITATION WITH CORNEAL INJURY.WHICH MAY RESULT IN PERMANENT IMPAIRMENT OF VISION, EVEN BLINDNESS.SKIN CONTACT: SHORT SINGLE EXPOSURE MAY CAUSE SEVERE SKIN BURNS .HAS CAUSED ALLERGIC REACTIONS IN HUMANS. DOT CLASSIFICATION: CORROSIVE . INHALATION: MAY CAUSE RESPIRATORY SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS. EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT. INGESTION: SINGLE DOSE ORAL TOXICITY IS LOW, THE ORAL LD 50 FOR RATS IS 4340 MG/KG. INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION OR ULCERATION. INGESTION MAY CAUSE BURNS OF MOUTH AND THROAT.

===== First Aid Measures =====

First Aid:EYES: CONTINUOUS FLOWING WATER FOR AT LEAST 30 MINUTES. SKIN: FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.CALL A PHYSICIAN.INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE AMOUNTS OF WATER OR MILK IF AVAILABLE. TRANSPORT TO MEDICAL FACILITY.INHALATION: REMOVE TO FRESH AIR IF EFFECTS OCCUR, CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:CALC
Flash Point:=-129.4C, 265.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL FOR SMALL FIRES. FOAM FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP AND DISPOSAL SHOULD BE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY SEALED.
Other Precautions:AVOID SKIN AND EYE CONTACT.

===== Exposure Controls/Personal P

rotection =====

Respiratory Protection:FRESH AIR MASK IN CONFINED SPACES.

Ventilation:LOCAL EXHAUST PREFERRED. MECHANICAL EXHAUST ACCEPTABLE.

RESPIRATORS AVAILABLE IF VENTILATION FAILS.

Protective Gloves:RUBBER OR PLASTIC.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:SAFETY SHOWER AND EYE BATH.

Supplemental Safety and Health

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS AND CHLOR

INATED COMPOUNDS

Hazardous Decomposition Products:NITROGEN OXIDES, CARBON DIOXIDE, AND

CARBON MONOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing th

is

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.