View NSN Online: https://aerobasegroup.de/nsn/8030-01-395-2726

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- POLYSULFIDE RUBBER COMPOUND PRO SEAL 870 C-12 BASE COMPOUND -- 8030-01-395-2726

Product ID:POLYSULFIDE RUBBER COMPOUND PRO SEAL 870 C-12 BASE COMPOUND

MSDS Date:09/06/1994

FSC:8030

NIIN:01-395-2726 Status Code:A

MSDS Number: CLQSZ === Responsible Party ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG

**INDUSTRIES COMPANY** 

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

====== Composition/Information on Ingre

dients =======

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

= Wt:15.

OSHA PEL:SEE TABLE Z-2 ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: POLYSULFIDE POLYMER

CAS:68611-50-7


Code:F

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000

= Wt:10.

OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3



EATING. AVOID INGESTION. Other Precautions: EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: WHEN APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR. Ventilation: GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL. Protective Gloves: SOLVENT RESIS TANT GLOVES. Eye Protection: CHEMICAL GOGGLES OR FULL FACE SHIELD. Other Protective Equipment: KEEP CONTAINER TIGHTLY CLOSED. Supplemental Safety and Health ======== Physical/Chemical Properties ============ Vapor Density:HEAVIER Spec Gravity: 1.43 VOC Pounds/Gallon:124 Appearance and Odor:BEIGE SEMI-LIQUID Percent Volatiles by Volume:21.7% ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Ha zardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, TRACES OF HYDROGEN SULFIDE. Conditions to Avoid Polymerization: WILL NOT OCCUR. ======= Disposal Considerations ============

Waste Disposal Methods: DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no ma

nner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.