

COURTAULDS AEROSPACE -- POLYURETHANE POLYMER COMPOUND PART B -- 8010-01-438-3671

=====  
Product Identification  
=====

Product ID:POLYURETHANE POLYMER COMPOUND PART B

MSDS Date:10/20/1998

FSC:8010

NIIN:01-438-3671

Status Code:A

MSDS Number: CLQTT

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone N

um:818-240-2060

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:0NYS9

=== Contractor Identification ===

Company Name:COURTAULDS AEROSPACE

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:0NYS9

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ISOBUTYL KETONE

CAS:108-10-1

RTECS #:SA9275000

&lt; Wt:5.

OSHA PEL:410 MG/M3;100 PPM

ACGIH TLV:205 MG/M3;

50 PPM  
ACGIH STEL:307 MG/M3;75 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:CARBONYL IRON  
CAS:7439-89-6  
RTECS #:NO4565500

Ingred Name:POLYURETHANE PREPOLYMER  
CAS:9042-82-4  
Code:F  
= Wt:15.

=====  
Hazards Identification  
=====

Effects of Overexposure:EYES: MAY CAUSE BURNING, TEARING, REDDENING,  
POSSIBLE TRANSIENT CORNEAL INJURY. SKIN: PROLONGED EXPOSURE MAY  
CAUSE DRYING AND CRACKING OF SKIN. POSSIBLE DERMATITIS. INHALATION:  
MAY CAUSE COUGHING, CHEST PAIN AND DIFFICULTY IN BREATHING.  
INGESTION: MAY CAUSE NAUSEA, VOMITING, ABDOMINAL DISCOMFORT AND  
DIARRHEA.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. IF SYMPTOMS  
PERSIST, CONSULT A PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND  
WATER. COVER EXPOSED AREAS WITH POLYETHYLENE GLYCOL WASH AGAIN WITH  
SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING  
STOPS, GIVE ARTIFICIAL RESPIRATION OR OXYGEN. CONSULT A PHYSICIAN.  
INGESTION: DO NOT INDUCE VOMITING. GIVE MILK OR WATER TO DRINK IF  
CONSCIOUS. CONSULT A PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point Method:SCC  
Flash Point:=-43.3C, 110.F  
Lower Limits:1.3%  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE  
WATER TO COOL HEAT EXPOSED CONTAINERS..  
Unusual Fire/Explosion

Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINER.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR AIR SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBENT MATERIAL, ADD DECONTAMINATION SOLUTION+AND ALLOW TO REACT FOR 10 MINUTES. COLLECT IN CONTAINERS, ADD ADDITIONAL DECONTAMINATION SOLUTION AND KEEP LOOSELY COVERED FOR 48 HOURS. CLEAN UP RESIDUE WITH A SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID MOISTURE CONTAMINATION WHICH WILL CAUSE CARBON DIOXIDE PRESSURE. DO NOT RESEAL CONTAINERS IF MOISTURE CONTAMINATION IS SUSPECTED.

Other Precautions:EMPTY DRUMS MAY CONTAIN SOME SOLVENT VAPORS DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES. DURING SPRAY APPLICATION, COMPLETE.

Eye Protection:GOGGLES OR FULL FACE SHIELD.

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHING. SAFETY SHOWER, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.

Supplemental  
Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:243-243 DEG F

Vapor Density:HEAVIER

Spec Gravity:3.67

Evaporation Rate & Reference:N-BUTYL ACETATE

Appearance and Odor:DARK GRAY VISCOUS LIQUID

Percent Volatiles by Volume:6.4%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
WATER, ALCOHOLS, STRONG BASES AMINES.

Hazardous Decomposition Products:OXIDES OF CARBON AND NIT

ROGEN,  
POSSIBLE TRACES OF HCN.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:EPA NO. D-001 HAZARDOUS WASTE. DISPOSE OF IN  
COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense.

The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.