

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3100 (PART B) -- 8030-00-881-2618

=====
Product Identification
=====

Product ID:CS 3100 (PART B)
MSDS Date:01/13/1999
FSC:8030
NIIN:00-881-2618
Status Code:A
Kit Part:Y
MSDS Number: CLQYP
=== Responsible Party ===
Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV
Address:11120 SHERMAN WAY
City:SUN VALLEY
State:CA
ZIP:91352-4949
Country:US
Info Phone Num:818-9
82-1650
Emergency Phone Num:(800)424-9300
Preparer's Name:HENRY SIMMONS
Chemtec Ind/Phone:(800)424-9300
CAGE:14439
=== Contractor Identification ===
Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV
Address:11120 SHERMAN WAY
Box:City:SUN VALLEY
State:CA
ZIP:91352-4949
Country:US
Phone:818-982-1650
CAGE:14439

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD OXIDE
CAS:1317-36-8
RTECS #:OG1750000
= Wt:6.

Ingred Name:LEAD DIOXIDE
CAS:1309-60-0
RTECS #:OG0700000

= Wt:64.

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-WEAKNESS, STUPOR. CHRONIC-KIDNEY
DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS.
Effects of Overexposure:HEADACHE, MUSCLE AND JOINT PAIN, NEUROMUSCULAR
DYSFUNCTION
Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

===== First Aid Measures =====

First Aid:INGESTION ? INDUCE VOMITING, CONSULT A PHYSICIAN AT ONCE. EYE
CONTACT: FLUSH WITH LARGE AMOUNT OF WATER AND CONTACT A PHYSICIAN

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>93.3C, 200.F
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER
Fire Fighting Procedures:USE A SELF CONTAINED BREATHING APPARATUS WITH
FULL FACE PIECE IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT WITH
OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND TRANSFER TO A SAFETY CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY AREA. KEEP
CONTAINERS CLOSED.
Other Precautions:WASH HANDS BEFORE EATING, DRINKING OR SMOKING.

===== Exposure Controls/Personal Protection =====

==

Respiratory Protection:IF SOOT IS FORMED USE NIOSH APPROVED RESPIRATOR
Ventilation:LOCAL EXHAUST- AIR HOOD, MECHANICAL- FAN
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES
Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT
Work Hygienic Practices:TRAIN PERSONNEL IN SAFE HANDLING OF THIS
PRODUCT
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=340.C, 644.F
Melt/Freeze Pt:M.P/F.P Text:LIQUID AT ROOM TEMP
ERATUR
Vapor Pres:NIL
Spec Gravity:3.00
pH:6.8
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWM PASTE, OILY ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZABLE MATERIALS
Stability Condition to Avoid:HIGH HEAT
Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGANICS.

===== Disposal Considerations =====

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT WITH
BASE AND DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibili

ty for the suitability of this information to their particular situation.