

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- PR 944F PART B --  
8030-01-398-7578

=====  
Product Identification  
=====

Product ID:PR 944F PART B

MSDS Date:02/16/1999

FSC:8030

NIIN:01-398-7578

Status Code:A

Kit Part:Y

MSDS Number: CLQYZ

=== Responsible Party ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:

CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

&lt;

Wt:5.  
ACGIH TLV:434 MG/M3;100 PPM  
ACGIH STEL:651 MG/M3;150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:DIMERCAPTO DIOXAOCANE  
CAS:14970-87-7  
&lt; Wt:5.

Ingred Name:CALCIUM CARBONATE @ LIMESTONE  
CAS:1317-65-3  
Code:F  
RTECS #:EV9580000  
= Wt:40.  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:2-PROPANOL, 1-METHOXY-, ACETATE  
CAS:108-65-6  
RTECS #:AI8925000  
&lt; Wt:5.

Ingred Name:ISOPROPYL ALCOHOL  
CAS:67-63-0  
RTECS #:NT8050000  
= Wt:5.  
OSHA PEL:980 MG/M3;400 PPM  
ACGIH TLV:983 MG/M3;4  
00 PPM  
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:MERCAPTAN TERMIN. POLYMER  
CAS:119147-89-6

Ingred Name:DIISODECYL PHTHLATE  
CAS:68515-49-1

Ingred Name:STEARIC ACID  
CAS:57-11-4  
RTECS #:WI2800000

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:XYLENE: EYES: MAY CAUSE BURNING,  
TEARING AND REDDENING. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING  
AND CRACKING OF SKIN POSSIBLE DERMATI

TIS. THIS PRODUCT MAY BE

ABSORBED THROUGH THE SKIN. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS AND FATIGUE. MAY CAUSE LIVER OR KIDNEY DAMAGE.

INGESTION: MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT. SIGNS OF NERVOUS SYSTEM DEPRESSION (DROWSINESS, DIZZINESS, LOSS OF COORDINATION, AND FATIGUE). ASPIRATION HAZARD THIS MATERIAL CAN ENTER LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION AND DAMAGE. 1,8-DIMERCAPTO-3, 6-DIOXAOCANE: EYES: SLIGHT REDDNESS

TO EYES. SKIN: NONIRRITATING TO SKIN. IN

Effects of Overexposure:INGESTION: MEDIAN LD50 835 MG/KG-ORAL RATS.

ISOPROPYL ALCOHOL: EYES: IRRITANT. SKIN: IRRITANT. INHALATION: MAY CAUSE NOSE AND THROAT IRRITATION. MAY CAUSE FLUSHING, HEADACHE, DIZZINESS, MENTAL DEPRESSION, NAUSEA, VOMITING, NARCOSIS ANESTHESIA AND COMA. INGESTION: MAY CAUSE HEADACHE, DIZZINESS, MENTAL DEPRESSION, NAUSEA, VOMITING, NARCOSIS, ANESTHESIA AND COMA. PROPYLENE GLYCOL METHYL ETHER ACETATE : EYES: M

AY CAUSE SLIGHT EYE

IRRITATION AND SLIGHT CORNEAL INJURY. SKIN: ESSENTIALLY NONIRRITATING TO SKIN. INHALATION: REPEATED EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT AND LIVER OR KIDNEY EFFECTS. INGESTION: SING

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES.CONSULT A PHYSICIAN.SKIN: WASH WITH SOAP AND WATER.CONSULT A PHYSICIAN.INHALATION: REMOVE TO FRESH AIR.CONSULT A PHYSICIAN.

INGESTION: CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=-22.2C, 72.F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE BUILD UP IN CLOSED CONTAINER.

===== Accidental Release Measures =====

=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL. COVER WITH ABSORBENT. SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT ELECTRICAL EQUIPMENT, SPARKS AND FLAME.  
Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING OR APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:SAFETY SHOWERS, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180-527 DEG F

Vapor Density:HEAVIER

Spec Gravity:1.285

VOC Pounds/Gallon:180

Appearance and Odor:WHITE LIQUID

Percent Volatiles by Volume:14.5%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:OXIDES OF CARBON.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Di

sposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.