View NSN Online: https://aerobasegroup.com/nsn/8010-00-558-7027

SHERWIN-WILLIAMS CO THE -- REDUCERS R7K58 -- 8010-00-558-7027

Product ID:REDUCERS R7K58 MSDS Date:08/19/1997 FSC:8010 NIIN:00-558-7027 Status Code:A MSDS Number: CLRTD === Responsible Party === Company Name: SHERWIN-WILLIAMS CO THE Address:101 PROSPECT AVE NW City:CLEVELAND State:OH ZIP:44115-1042 Country:US Info Phone Num:800-251-2486/216-566-2242 **Emergency Phon** e Num:216-566-2917 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:54636 === Contractor Identification === Company Name: SHERWIN-WILLIAMS CO THE Address:101 PROSPECT AVE NW Box:City:CLEVELAND State:OH ZIP:44115-1042 Country:US Phone:800-251-2486/216-566-2242 CAGE:54636

Ingred Name:2-PROPANOL, 1-METHOXY-, ACETATE CAS:108-65-6 RTECS #:AI8925000 = Wt:28.

Ingred Name:XYLENE CAS:1330-20-7 RTECS #:ZE2100000 = Wt :42. ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3;150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL N-AMYL KETONE CAS:110-43-0 RTECS #:MJ5075000 = Wt:23. OSHA PEL:465 MG/M3;100 PPM ACGIH TLV:233 MG/M3:50 PPM

Ingred Name:ETHYLBENZENE CAS:100-41-4 RTECS #:DA0700000 = Wt:7. OSHA PEL:435 MG/M3;100 PPM ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:543 MG/M3;125 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes

of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic: EXPOSURE MAY BE BY INHALATION AND/ OR SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. ALCOHOLS AND ACETATES IN BUTYL CELLOSOLVE, HAPS COMPLYING DYE STAIN REDUCER, REDUCER 54 AND REDUCER58 CAN BE ABSORBED THROUGH THE SKIN. TO MINIMIZE EXPOSURE, FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.
Effects of Overexposure: IRRITATION OF EYES, SKIN AND RESPIRA TORY

SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH. HEADACHE DIZZINESS, NAUSEA, AND LOSS OF COO RDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

First Aid: IF INHALED:

IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. IF ON SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE -USE. IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. IF SWALLOWED: NEVER GIVE AYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE SEVERAL GLAS SES OF WATER. SEEK MEDICAL ATTENTION.

Flash Point:=26.7C, 80.F Lower Limits: 1.0% Upper Limits:19.0% Extinguishing Media: CARBON DIOXIDE DRY CHEMICAL, FOAM. Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CO NTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITIONOR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. **Unusual Fir** e/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIA L PRECAUTIONS. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY. DURING USE AND UNTIL ALL VAPORS ARE GONE: KEEP AREA VENTILATED DO NOT SMOKE EXTINGUISH ALL FLAM ES, PILOT, LIGHTS, AND HEATERS TURN OFF STOVES, ELECTRIC TOOLS AND APPLIANCES, AND ANY OTHER SOURCES Other Precautions: INTENTIONAL MISUSE BY DELIBERATELY CON

## CENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS I N SECTION II.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION II IS

MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVE SUPPLIER FOR PROTECTION.

Eye Protection:WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS. Supplemental Safety and Health

Boiling Pt:B.P. Text:132-340 F Vapor Density:HEAVIER Spec Gravity:0.79-0.90 VOC Grams/Liter:7.28 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:100%

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:WASTE FROM THESE PRODUCTS MAY BE HAZARDOUS AS DEFINED UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT (RCRA) 40 CFR 261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOU S WASTE NUMBERS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULAT

State Regulatory Information:CALIFORNIA PROPOSITION 65: WARNING: ACETONE CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. REDUCER 54 AND REDUCER 58 CONTAIN CHEMICALS KN OWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify a nd

assume responsibility for the suitability of this information to their particular situation.