

SHERWIN-WILLIAMS CO THE -- INVERTED MARKING PAINTS-4 -- 8010-01-418-7646

=====
Product Identification
=====

Product ID:INVERTED MARKING PAINTS-4
MSDS Date:08/17/1998
FSC:8010
NIIN:01-418-7646
Status Code:A
MSDS Number: CLRWH
=== Responsible Party ===
Company Name:SHERWIN-WILLIAMS CO THE
Address:101 PROSPECT AVE NW
City:CLEVELAND
State:OH
ZIP:44115-1042
Country:US
Info Phone Num:800-251-2486/216-56
6-2242
Emergency Phone Num:216-566-2917
Preparer's Name:ERNEST CARTER
Chemtrec Ind/Phone:(800)424-9300
CAGE:54636

=== Contractor Identification ===
Company Name:SHERWIN-WILLIAMS CO THE
Address:101 PROSPECT AVE NW
Box:City:CLEVELAND
State:OH
ZIP:44115-1042
Country:US
Phone:800-251-2486/216-566-2242
CAGE:54636

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
= Wt:13.
OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:BUTANE
CAS:106-97-

8

RTECS #:EJ4200000

= Wt:12.

ACGIH TLV:800 PPM

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)

CAS:64742-89-8

= Wt:7.

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

= Wt:10.

OSHA PEL:SEE TABLE Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE

CAS:67-64-1

RTECS #:AL3150000

= Wt:20.

OSHA PEL:2400 MG/M3;1000 PPM

ACGIH TLV:500 PPM

ACGIH STEL:750 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. TO MINIMIZE EXPOSURE, FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.

Effects of Overexposure:IRRITATION OF EYES, SKIN AND RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY

DEATH. HEADACHE,

DIZZINESS, NAUSEA, AND LOSS OF CO ORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN

EXPOSURE.CHRONIC HEALTH HAZARD: NO INGREDIENT IN THESE PRODUCTS IS AN IARC, NTP OR OSHA LISTED CARCINOGEN. PROLONGED AND REPEATED EXPOSURE TO MAY CAUSE DAMAGE TO NERVOUS TISSUE OF THE AREAS AND LEGS RESULTING IN MUSCULAR WEAKNESS AND LOSS OF SENSATI ON. THIS EFFEC

T MAY BE IN

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

=====
===== First Aid Measures =====

First Aid:IF INHALED: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. IF ON SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE RE USE. IF IN EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. IF SWALLOWED: NEVER GIVE ANY THING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE SEVERAL GLASSES OF WATER. GET MEDICALATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=-28.7C, -20.F

Lower Limits:0.9%

Upper Limits:27.0%

Extinguishing Media:CARBON DIOXIDE,, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER

IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CO NTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. APPLICATIONS TO HOT SURFACES REQUIRES SPEC IAL PRECAUTIONS. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:CONTENTS ARE EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY. DURING USE AND UNTIL V

APORS ARE

GONE: KEEP AREA VENTILATED. D O NOT SMOKE EXTINGUISH ALL FLAMES,
PILOT LIGHTS, AND HEATERS TURN OFF STOVES, ELECTRIC TOOLS AND AP

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING
AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. CONTENTS UNDER
PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPARATURE
ABOVE 120 DEG F. SU NLIGHT, STOVES, RADIATORS, HOT WATER, AND OTHER
HEAT SOURCES CAN CAUSE CONTAINERS TO BURST. TO NOT T AKE
INTERNAL
LY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW
APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC
VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION
AGAINST MATERIALS I N SECTION II.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE
EXPOSURE TO MATERIALS IN SECTION II IS MAINTAINED BELOW APPLICABLE
EXPOSURE LIMITS.

Protective G

loves:WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVE SUPPLIER
FOR PROTECTION.

Eye Protection:WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.

Other Protective Equipment:USE ONLY WITH ADEQUATE VENTILATION. AVOID
BREATHING VAPORS AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.
WASH HANDS AFTER USING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text: